

Product Datasheet

16-Port Full Gigabit Managed Industrial Ethernet Switch

(IND-D-M-FG-1204-N)



OVERVIEW

The IND-D-M-FG-1204-N is a full gigabit managed industrial Ethernet switch. It has 12*10/100/1000M RJ45 ports and 4*100/1000M SFP port slots. It can support L2+ full network management function, IPV4/IPV6 management, rich network management features, and complete network security policy configuration, it is suitable for intelligent transportation, rail transit, electric power, mining, metallurgy, and green energy construction.

The IND-D-M-FG-1204-N can support multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS (<20ms) industrial fast ring network protocol. When the one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. It has high reliability, high security, high manageability, ensuring reliable transmission of critical data, support for

remote management, and can be used for cluster management with NMS network management platform. No blind spot network management. IND-D-M-FG-1204-N industrial grade series products fully comply with industrial product design and materials. The shell is made of aluminum alloy to enhance heat dissipation performance and has excellent industrial field environment adaptability (including mechanical stability, climatic environment adaptability, electromagnetic environment adaptation). Sexuality, protection level up to IP40, support for dual redundant power supply, low power consumption fanless cooling technology, MTBF mean time between failures of up to 35 years, long 5 years warranty.

FEATURE

■ Gigabit access, SFP port uplink

- ◇ All series supports Ethernet port and SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

■ Strong business processing capability

- ◇ IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN and QinQ configuration.
- ◇ QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including Equ, SP, WRR & SP+WRR.
- ◇ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.
- ◇ IGMP V1/V2 and IGMP Snooping.
- ◇ ERPS/STP/RSTP/MSTP.
- ◇ Static and dynamic aggregation.

■ Security

- ◇ 802.1X authentication.
- ◇ Port isolation, Storm control.
- ◇ IP-MAC-VLAN-Port binding.

■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ Low power consumption, no fan, aluminum casing.
- ◇ The user-friendly panel, it can show the device status through the LED indicator of PWR, SYS, Link, L/A.

■ Easy operation and maintenance management

- ◇ HTTPS, SSLV3, and SSHV1/V2.
- ◇ RMON, system log, LLDP, and port traffic statistics.
- ◇ CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- ◇ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

TECHNICAL SPECIFICATION

Model	IND-D-M-FG-1204-N
Interface Characteristics	
Fixed Port	12*10/100/1000Base-T uplink RJ45 ports (Data) 4*100/1000Base-X uplink SFP slot ports (Data) 1 * RS232 console port(115200,N,8,1) 2 set of V+, V- redundant DC power interface (6 Pin Phoenix terminal) Alarm switch (FAULT)
Ethernet Port	Port 1-12 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption
Twisted Pair	10BASE-T: Cat3,4,5 UTP(≤100 meter)
Transmission	100BASE-TX: Cat5 or later UTP(≤100 meter)


	1000BASE-T: Cat5e or later UTP(≤100 meter)
Optical Fiber Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable/ Distance	Multi mode: 850nm / 0 ~ 500M, single mode: 1310nm / 0 ~ 40KM, 1550nm / 0 ~ 120KM.
Chip Parameter	
Network Management Type	L2+
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX , IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	256Gbps
Forwarding Rate@64byte	23.81Mpps
MAC	8K
Buffer Memory	6M
Jumbo Frame	9.6K
LED Indicator	Power: PWR (green), System: SYS (green), Network: Link/Act (yellow), Fiber Port : L/A (green)
Reset Switch	Yes, One-button factory reset
Power	
Total PWR / Input Voltage	<24W /(48VDC)
Power Consumption	Standby<10W, Full load<22W
Working Voltage	12-48VDC, 6 Pin industrial Phoenix terminal, support anti-reverse protection.

Power Supply	No, optional 24V/24W or 24V/36W industrial power supply
Physical Parameter	
Operation TEMP / Humidity	-40~+80°C;5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+85°C;5%~95% RH Non condensing
Dimension (L*W*H)	166*148*54mm
Net /Gross Weight	<1.2kg / <1.5kg
Installation	Desktop, DIN rail
Certification & Warranty	
Lightning protection / protection level	Lightning protection: 6KV 8/20us; Protection level: IP40 IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge IEC61000-4-3(RS):10V/m(80~1000MHz) IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz) IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s IEC61000-4-9(pulsed magnet field):1000A/m IEC61000-4-10(damped oscillation):30A/m 1MHz IEC61000-4-12/18(shockwave):CM 2.5kV,DM 1kV IEC61000-4-16(common-mode transmission):30V; 300V,1s FCC Part 15/CISPR22(EN55022):Class A IEC61000-6-2(Common Industrial Standard)
Mechanical Properties	IEC60068-2-6 (anti vibration) IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall)
Certification	CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS;


Warranty	5 years, lifelong maintenance.
Network Management Features	
Interface	IEEE802.3X (Full-duplex) Port temperature protection setting Port green Ethernet Energy-saving setting Broadcast storm control based on port speed The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.
Layer 3 Features	L2+ network management ,IPV4/IPV6 management L3 soft routing forwarding, Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	4K VLAN based on port, IEEE802.1q VLAN based on the protocol VLAN based on MAC Voice VLAN, QinQ configuration Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation Max 8 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)
Industrial Ring	G.8032 (ERPS),Recovery time less than 20ms
Network Protocol	250 Ring at most, Max 1024 devices per ring.
Multicast	MLD Snooping v1/v2,Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS,Priority Mark/Remark

	Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL, ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection, Anti-DoS attack AAA & RADIUS, MAC learning limit Mac black holes, IP source protection IEEE802.1X & MAC address authentication Broadcast storm control, Backup for host datum SSH 2.0, SSL, Port isolation, ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	One-key recovery Cable Diagnose, LLDP Web Management (HTTPS) NTP, System work log, Ping Test CPU instant utilization status view Console/AUX Modem/Telnet/SSH2.0 CLI Download & Management on FTP, TFTP, Xmodem, SFTP, SNMP V1/V2C/V3 NMS - smart network management system platform (LLDP+SNMP)
System	Category 5 Ethernet network cable Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer 10 or later; TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

DIMENSION



APPLICATION



ORDERING INFORMATION

Model	Description	Recommended Power Supply
IND-D-M-FG-1 204-N	L2+ managed industrial Ethernet fiber switch with 12*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. It can support dual DC power supply input and DIN rail mounting.	24W/36W

Note: Industrial Ethernet switch does not match the power supply and SFP module by default.

PACKING LIST

	CONTENT	QTY	UNIT
PACKING LIST	16-port full gigabit managed industrial Ethernet switch	1	SET
	RJ45-DB9 Line	1	PC
	User Guide	1	PC
	Warranty Card	1	PC

OPTICAL MODULE INFORMATION

Product	Model	Description	Unit
1.25G Optical Module	2630	SFP optical module, 1.25G, multi mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM function, support hot plug and pull.	PC
	2632	SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC

	2612-T	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2613-R	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2612-T-G	Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2613-R-G	Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2612-T-SC	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
	2613-R-SC	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
Power Module	2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.	PC

POWER SUPPLY SELECTION TABLE

Product	Model	Description	Unit
24W DIN Rail Industrial Power Supply	DP24-24	Din Rail type 24W single set of output power supply; Input Voltage:AC 100V~240V 50-60H,0.35A Output Voltage:DC 24V 1.0A Operation Temperature: -40°C—+70°C	PC

36W DIN Rail Industrial Power Supply	DP36-24	Din Rail type 36W single set of output power supply; Input Voltage:AC 100V~240V 50-60Hz, 1A Output Voltage:DC 24V 1.5A Operation Temperature:-40°C—+70°C	PC
--	---------	--	----

RELATED PRODUCT

Model	Description
IND-D-M-FG-0402-N	L2+ managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 2*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting.
IND-D-M-FG-0404-N	L2+ managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting.
IND-D-M-FG-0802-N	L2+ managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 2*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting.
IND-D-M-FG-1004-N	L2+ managed industrial Ethernet fiber switch with 10*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting.
IND-D-M-FG-0808-N	L2+ managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 8*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting.
IND-D-M-FG-2004-N	L2+ managed industrial Ethernet fiber switch with 20*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting.



CONTACT US

AUTOMATION SYSTEMS & SOLUTION

Address: T-12, 3rd Floor, Pankaj Central Market, I.P. Extension,
Patparganj, **Delhi – 110092**

Tel: +91 11 41709077 / 22232187

Email: infoautomation18@gmail.com

Website: www.automationsystem.in